



PACO (page 1)

Part Number	LPF40030318D	LPF40060336D	LPF40060645D	LPF40120345D	LPF40120672D
Description	LED PACO Panel 18W 300X300(4000K) Dali Dimmable	LED PACO Panel 36W 600X300(4000K) Dali Dimmable	LED PACO Panel 45W 600X600(4000K) Dali Dimmable	LED PACO Panel 45W 1200X300(4000K) Dali Dimmable	LED PACO Panel 72W 1200X600(4000K) Dali Dimmable
Chipset	Hongli 2835	Hongli 2835	Hongli 2835	Hongli 2835	Hongli 2835
Driver	LEDified UP 180450-DALI1	LEDified UP 450100-DALI2	LEDified UP 450100-DALI2	LEDified UP 450100-DALI2	LEDified
Dimmable	Yes – Dali	Yes – Dali	Yes – Dali	Yes – Dali	Yes – Dali
Nominal Power	18W	36W	45W	45W	72W
Input Voltage Tolerance	220-240V AC	220-240V AC	220-240V AC	220-240V AC	220-240V AC
Nominal Lumens (LM)	1260	2520	3150	3150	5040
Nominal Efficacy (LM/W) / PF	70/ >0.9	70/ >0.9	70/ >0.9	70/ >0.9	70/ >0.9
Colour Temperature / CRI	4000K (Neutral White) / Ra80	4000K (Neutral White) / Ra80	4000K (Neutral White) / Ra80	4000K (Neutral White) / Ra80	4000K (Neutral White) / Ra80
Beam Angle / UGR Index	120°/ 19	120°/ 19	120°/ 19	120°/ 19	120°/ 19
Dimensions (MM) / Weight (G)	295X295X10 / 3500	595X295X10 / 4500	595X595X10 / 5500	295X1195X10 / 5500	595X1195X10 / 11000
Cut Out Size (MM)	280X280	280X580	580X580	280X1180	580X1180
Working Temperature	-20°C – 45°C	-20°C – 45°C	-20°C – 45°C	-20°C – 45°C	-20°C – 45°C
Expected Life Time	>50,000 Hours	>50,000 Hours	>50,000 Hours	>50,000 Hours	>50,000 Hours
Warranty	5	5	5	5	5
IP Rating / IK Rating	IP40 / Test Pending	IP40 / Test Pending	IP40 / Test Pending	IP40 / Test Pending	IP40 / Test Pending



PACO (page 2)

Part Number	LPF65030318D	LPF65060336D	LPF65060645D	LPF65120345D	LPF65120672D
Description	LED PACO Panel 18W 300X300(6500K) Dali Dimmable	LED PACO Panel 36W 600X300(6500K) Dali Dimmable	LED PACO Panel 45W 600X600(6500K) Dali Dimmable	LED PACO Panel 45W 1200X300(6500K) Dali Dimmable	LED PACO Panel 72W 1200X300(6500K) Dali Dimmable
Chipset	Hongli 2835	Hongli 2835	Hongli 2835	Hongli 2835	Hongli 2835
Driver	LEDified UP 180450-DALI1	LEDified UP 450100-DALI2	LEDified UP 450100-DALI2	LEDified UP 450100-DALI2	LEDified
Dimmable	Yes – Dali	Yes – Dali	Yes – Dali	Yes – Dali	Yes – Dali
Nominal Power	18W	36W	45W	45W	72W
Input Voltage Tolerance	220-240V AC	220-240V AC	220-240V AC	220-240V AC	220-240V AC
Nominal Lumens (LM)	1350	2700	3375	3375	5400
Nominal Efficacy (LM/W) / PF	75/ >0.9	75/ >0.9	75/ >0.9	75/ >0.9	75/ >0.9
Colour Temperature / CRI	6500K(Daylight White) / Ra80	6500K(Daylight White) / Ra80	6500K(Daylight White) / Ra80	6500K(Daylight White) / Ra80	6500K(Daylight White) / Ra80
Beam Angle / UGR Index	120°/ 19	120°/ 19	120°/ 19	120°/ 19	120°/ 19
Dimensions (MM) / Weight (G)	295X295X10 / 3500	595X295X10 / 3500	595X595X10 / 5500	295X1195X10 / 5500	595X1195X10 / 11000
Cut Out Size (MM)	280X280	280X580	580X580	280X1180	580X1180
Working Temperature	-20°C – 45°C	-20°C – 45°C	-20°C – 45°C	-20°C – 45°C	-20°C – 45°C
Expected Life Time	>50,000 Hours	>50,000 Hours	>50,000 Hours	>50,000 Hours	>50,000 Hours
Warranty	5	5	5	5	5
IP Rating / IK Rating	IP40 / Test Pending	IP40 / Test Pending	IP40 / Test Pending	IP40 / Test Pending	IP40 / Test Pending